

**FORMULA:**  $C_3H_7N(CH_3)_2$

**MOL WT:** 87.16

### **DESCRIPTION**

Dimethylisopropylamine (DMIPA) is a low molecular weight tertiary amine. It is generally used in the automotive foundry industry. The product is a colorless substance and has a strong ammoniacal odor.

### **APPLICATIONS**

Chemical intermediates, catalysis, polymer formulations, rubber chemicals, resin curing in foundries (Cold Box process).

### **SPECIFICATIONS**

### **TEST METHOD**

Purity, wt. %	99.2	Min.	MP-1100
Water, wt. %	0.2	Max.	MP-1116
<b>Impurities:</b>			MP-1100
Isopropanol, wt. %	0.3	Max.	
Diisopropylmethylamine, wt. %	0.8	Max.	
Methylisopropylamine, wt. %	0.1	Max.	
Density @ 20°C, g/mL	0.707 ± 0.02		MP-1118

### **Notes:**

N/A

### **AVAILABILITY**

In bulk or drums containing 200 L (52.85 gal).



Unidad Industrial Irapuato

## SALES SPECIFICATION

EVC-904

DIMETHYLISOPROPYLAMINE

01/05/21

2 of 2

Revision

02

**Headquarters:** Bosque de Radiatas No. 34, Bosques de las Lomas, Cuajimalpa de Morelos, C.P. 05120, CDMX, Tel. 55 2789-2200 Fax: 55 2789-2351

**IRAPUATO Plant:** Av. Salamanca 1843 Cd. Industrial de Irapuato C.P. 36540 Irapuato, Gto., Tel. 462 622 5087 Fax 462 622 5088

### Website

[www.grupoidesa.com](http://www.grupoidesa.com)

### Email

**Commercial:** [pedidosidesa@idesa.com.mx](mailto:pedidosidesa@idesa.com.mx) **Quality:** [calidesa@idesa.com.mx](mailto:calidesa@idesa.com.mx)